

# Sanimarin Maxlite **+S**

COMPACT RANGE

Thanks to the use of pressurised water on board, this quiet toilet offers maximum comfort. Being ultra-efficient, it can be integrated into all types of configurations.



..... MAXIMUM COMFORT .....

## TECHNICAL FEATURES

PUMPING HEIGHT	3 m
HORIZONTAL PUMPING DISTANCE	30 m
NON RETURN VALVE	Integrated
OUTLET DIAMETER	38 mm or 25 mm
SUPPLY VOLTAGE	12 V or 24 V DC
MOTOR POWER	300 W (12 V), 360 W (24 V)
ELECTRICITY CONSUMPTION	0,007 Ah (12 V) and 0,004 Ah (24 V) per second (see detail p.26)
WATER CONSUMPTION	Quantity decided by the user
WATER USE	Integrated solenoid valve for connection to the pressurized water system on board.
WEIGHT	8 kg

## 1 CONTROL SYSTEM



The electric switch Comfort

06

07



Features SFA macerating technology (stainless steel blade)



Connection to the pressurised water onboard



Easy to use



Enables variable positioning of the bowl



Reversible motor/pump unit for right or left hand installation



Soft close seat



Ultra-light material used for bowl construction

## TECHNICAL VIEW



Solenoid valve included

## DIMENSIONS (mm)

