


Geberit Dämmschlauch aus PE



Beispielbild

Verwendungszwecke

- Zur Körperschalldämmung von Rohren
- Zur UP-Montage

Eigenschaften

- Klasse E nach DIN EN 13501-1

Technische Daten

Werkstoff

PE-E

Art.-Nr.	DN	d, Ø	di, Ø	s	L	VE1	VE2	VE3
305.921.00.1	56 / 60	56 / 63 mm	74 mm	4 mm	15 m	15 m	150 m	
306.921.00.1	60 / 70	63 / 75 mm	83 mm	4 mm	15 m			
307.921.00.1	70 / 90	75 / 90 mm	97 mm	4 mm	15 m	15 m	150 m	300 m
308.921.00.1	90 / 100	90 / 110 mm	121 mm	4 mm	15 m	15 m	150 m	300 m
310.921.00.1	100 / 125	110 / 135 mm	145 mm	4 mm	15 m	15 m	120 m	240 m
312.921.00.1	125	135 mm	155 mm	4 mm	15 m	15 m	75 m	



UNIDOMO®

- Lieferung in Rollen



Web: www.unidomo.de

Telefon: 04621- 30 60 89 0

Mail: info@unidomo.com

Öffnungszeiten: Mo.-Fr. 8:00-17:00 Uhr

VIESSMANN



 **Vaillant**

WOLF

 **JUNKERS**  **BOSCH**

 **remeha**

 **DAIKIN**

ROTEX
a member of DAIKIN group



-  Individuelle Beratung
-  Kostenloser Versand
-  Hochwertige Produkte

-  Komplettpakete
-  Über 15 Jahre Erfahrung
-  Markenhersteller