



HANSAPRIMO

Installation and maintenance guide



Ihr Online-Fachhändler für:

- Kostenlose und individuelle Beratung
- Hochwertige Produkte
- Kostenloser und schneller Versand
- TOP Bewertungen
- Exzelerter Kundenservice
- Über 20 Jahre Erfahrung



E-Mail: info@unidomo.de | Tel.: 04621 - 30 60 89 0 | www.unidomo.de




4-9



10-17



18



18-23




24



4940 2203


I (ISO 3822)
EN 817
50 - 1000 kPa
0.10 l/s (300 kPa w/Controller)
max. +70°C



mpi.hansa.com/49402203

4942 2203 , 4942 2203 0037


I (ISO 3822)
EN 817
100 - 1000 kPa
0.10 l/s (300 kPa w/Controller)
200 kPa (0.1 l/s)
max. +70°C



mpi.hansa.com/49422203

4956 2203 , 4956 2203 00676


I (ISO 3822)
EN 817
50 - 1000 kPa
0.10 l/s (300 kPa w/Controller)
max. +70°C



mpi.hansa.com/49562203

4937 2203


I (ISO 3822)
 EN 817
 100 - 1000 kPa
 0.10 l/s (300 kPa w/Controller)
 200 kPa (0.1 l/s)
 max. +70°C



mpi.hansa.com/49372203

4946 2203


I (ISO 3822)
 EN 817, EN 1113
 100 - 1000 kPa
 0.15 l/s (300 kPa)
 0.10 l/s (300 kPa w/Controller)
 200 kPa (0.1 l/s)
 max. +70°C



mpi.hansa.com/49462203

4943 3203


I (ISO 3822)
 EN 817
 50 - 1000 kPa
 0.10 l/s (300 kPa w/Controller)
 max. +70°C



mpi.hansa.com/49433203

**4938 1103**


EN 817
50 - 500 kPa
max. +80°C



mpi.hansa.com/49381103

4957 1103


EN 817
50 - 500 kPa
max. +80°C



mpi.hansa.com/49571103

4922 1103


EN 817
50 - 500 kPa
max. +80°C



mpi.hansa.com/49221103

4948 2203 , 4948 2203 00676


I (ISO 3822)
EN 817
50 - 1000 kPa
0.20 l/s (300 kPa)
300 kPa (0.2 l/s)
max. +70°C



mpi.hansa.com/49482203

4954 2203


I (ISO 3822)
EN 817
50 - 1000 kPa
0.10 l/s (300 kPa w/Controller)
max. +70°C



mpi.hansa.com/49542203

4920 2203 , 4920 2203 0037

I (ISO 3822)
EN 817
100 - 1000 kPa
0.20 l/s (300 kPa)
max. +70°C




mpi.hansa.com/49202203



4955 2203



I (ISO 3822)
EN 817
100 - 1000 kPa
0.10 l/s (300 kPa w/Controller)
max. +70°C



mpi.hansa.com/49552203

4950 2203


I (ISO 3822)
EN 817
50 - 1000 kPa
0.20 l/s (300 kPa)
300 kPa (0.2 l/s)
max. +70°C



mpi.hansa.com/49502203

4949 1103

I (ISO 3822)
EN 817
50 - 500 kPa
0.12 l/s (300 kPa)
max. +70°C




mpi.hansa.com/49491103



4944 2103 , 4944 2103 00003



I (ISO 3822)
EN 817
100 - 1000 kPa
0.34 / 0.32 l/s (300 kPa)
250 kPa (0.3 l/s)
max. +80°C



mpi.hansa.com/49442103

4945 0103


I (ISO 3822)
EN 817
100 - 1000 kPa
0.28 l/s (300 kPa)
160 kPa (0.2 l/s)
max. +80°C









mpi.hansa.com/49450103

4951 2203


EN 817
50 - 1000 kPa
0.34 / 0.32 l/s (300 kPa)
max. +70°C







mpi.hansa.com/49512203








1






1







max.
1600 kPa



1









①

max.
1600 kPa





②






1 2 3 4




A









③④⑤

B








max.
1600 kPa











① ② ③



①








②




A





A













A




B







2






A1












G1



G2




G6








① ②






③



③





CLEANING.HANSA.COM



Ihr Online-Fachhändler für:

- Kostenlose und individuelle Beratung
- Hochwertige Produkte
- Kostenloser und schneller Versand
- TOP Bewertungen
- Exzelerter Kundenservice
- Über 20 Jahre Erfahrung



E-Mail: info@unidomo.de | Tel.: 04621 - 30 60 89 0 | www.unidomo.de

Oras Group is a powerful European provider of sanitary fittings: the market leader in the Nordics and a leading company in Continental Europe. The company's mission is to make the use of water easy and sustainable and its vision is to become the European leader of advanced sanitary fittings. Oras Group has two strong brands: Oras and Hansa.

The Group's head office is located in Rauma, Finland, and the Group has three manufacturing sites: Kralovice (Czech Republic), Olesno (Poland) and Rauma (Finland). Oras Group employs approximately 1,200 people in twenty countries. Oras Group is owned by Oras Invest, a family company and an industrial owner.

HANSA Armaturen GmbH
P. O. BOX 81 02 40
D-70519 Stuttgart
Sigmaringer Strasse 107
D-70567 Stuttgart
Tel.: +49 711 16 14 0
Fax: +49 711 16 14 368
info@hansa.de
www.hansa.com



943375D-01-22