

Zertifikat *Certificate*

Zertifikatsnummer *Certificate No.:*

PV 50671369 0001

Berichtsnummer *Report No.:*

CN24LDFA 035

Genehmigungsinhaber *License Holder:*

Viessmann Climate Solutions
GmbH & Co. KG
Viessmannstr. 1
35108 Allendorf (Eder)
Deutschland

Fertigungsstätte *Manufacturing Site:*

040-0002146145

Prüfzeichen *Test Mark:*

Geprüft nach *Tested according to:*

IEC 61215-1:2021
IEC 61215-1-1:2021
IEC 61215-2:2021
IEC 61730-1:2023
IEC 61730-2:2023
EN IEC 61215-1:2021
EN IEC 61215-1-1:2021
EN IEC 61215-2:2021
EN IEC 61730-1:2018
EN IEC 61730-2:2018

Geräteidentifikation
Product Identification

Produkt: PV Module
Product:

Modell: Modelle sind auf nächste(r) Seite(n) gelistet
Type: *Type designation(s) are listed on the next page(s)*

Technische Daten: Class II acc. to IEC 61140
Technical Data: For other ratings, refer to the test report

Gültig bis: 2029-04-02
Date of expiry:

Gültig ab: 2025-04-08
Valid from:

Ausstellungsdatum: 2025-04-08
Date of issue:

Zertifizierungsstelle:
Certification body:

Angela Yao



Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product fulfills above mentioned requirements, the production is subject to surveillance.

TÜV Rheinland LGA Products GmbH, Tillystraße 2, 90431 Nürnberg

<http://www.tuv.com/safety> E-mail: markcheck@tuv.com

Fax: +49 221 806-3935

www.tuv.com

 **TÜVRheinland®**
Precisely Right.



Ihr Online-Fachhändler für:

VIESSMANN

- Kostenlose und individuelle Beratung
- Hochwertige Produkte
- Kostenloser und schneller Versand

- TOP Bewertungen
- Exzellerter Kundenservice
- Über 20 Jahre Erfahrung



E-Mail: info@unidomo.de | Tel.: 04621 - 30 60 89 0 | www.unidomo.de

Zertifikat *Certificate*

Zertifikatsnummer *Certificate No.:*

PV 50671369 0001

Berichtsnummer *Report No.:*

CN24LDFA 035

Produkt *Product:* PV Module

Modell *Type:*

Bezeichnung *Designation:*

Max. System Voltage: up to 1500 VDC (Voc at STC):

With ½ cut of N-type mono c-Si cells:

Vitovolt 300-DG Mxxx AO Blackframe (xxx=425-455, in steps of 5, 108cells)

Vitovolt 300-DG Mxxx AO Allblack (xxx=425-455, in steps of 5, 108cells)

Vitovolt 300-DG Mxxx AO (xxx=430-460, in steps of 5, 108 cells)

Vitovolt 300-DG Mxxx AR (xxx=480-515, in steps of 5, 120 cells)

Vitovolt 300-DG Mxxx AR Blackframe (xxx=480-515, in steps of 5, 120cells)

Vitovolt 250-DG Mxxx AS (xxx=585-630, in steps of 5, 132 cells)

Vitovolt 300-DG Mxxx AT Allblack (xxx=440-455, in steps of 5, 96cells)

Vitovolt 300-DG Mxxx AT Blackframe (xxx=440-455, in steps of 5, 96cells)

Vitovolt 300-DG Mxxx AT Blackview (xxx=440-455, in steps of 5, 96cells)

Vitovolt 300-DG Mxxx AU (xxx=495-515, in steps of 5, 108 cells)

Vitovolt 300-DG Mxxx AU Blackview (xxx=495-510, in steps of 5, 108cells)

xxx represents output power in Wp

Remarks:

Fire Rating: Class A or C (according to UL 790)

Design Load/Safety Factors: 3600 Pa / 1.5 (downward)

1600 Pa / 1.5 (upward)

Conditions:

The product test is voluntarily according to technical regulations.
Any change of the design, materials, components or processing may
require the repetition of some of the qualification tests in order
to retain type approval.

