

Planning and installation

# Overhead showers and shower systems



**UNIDOMO®**

**Web:** [www.unidomo.de](http://www.unidomo.de)

**Telefon:** 04621- 30 60 89 0

**Mail:** [info@unidomo.com](mailto:info@unidomo.com)

**Öffnungszeiten:** Mo.-Fr. 8:00-17:00 Uhr

**VIESSMANN**

**Buderus**

 **Vaillant**

**WOLF**




 **JUNKERS**  **BOSCH**




 **remeha**

 **DAIKIN**

**ROTEX**  
a member of **DAIKIN** group



-  Individuelle Beratung
-  Kostenloser Versand
-  Hochwertige Produkte

-  Komplettpakete
-  Über 15 Jahre Erfahrung
-  Markenhersteller







# Table of contents

---

4	Hansgrohe for Professionals
10	System 1: 1-spray showers – Like showering in rain Raindance® overhead showers for ceiling and wall installation
14	System 2: 2-spray overhead showers – Stylish and ergonomic Raindance® Rainfall® 180 2jet and Raindance® E 420 2jet for installation on the wall
18	System 3: 3-spray overhead showers – Variety for body and soul Raindance® Rainfall® 3jet for wall installation and Raindance® Rainmaker® for installation flush with the ceiling
34	System 4: Showerpipes – The simple way to intense shower pleasure Raindance® Showerpipes for exposed and concealed installation for showers or bath tubs. Raindance® Connect Showerpipe for mounting onto existing mixers.
46	iBox® universal – The simple solution for concealed installation Possible combinations and brief installation instructions
48	Hansgrohe and Axor finish sets – Combinations and product lines Thermostats, shut-off and diverter valves
52	RainBrain® – The intelligent shower control Electronic control unit with touch-screen function Planning and installation instructions




# Hansgrohe for Professionals

---

## **We are partners**

Hansgrohe supports the professional partners through a wide range of services.

Make sure to benefit from our comprehensive knowledge.



**Find out more on our website:**  
**[pro.hansgrohe-int.com](http://pro.hansgrohe-int.com)**



Hansgrohe for  
Professionals  
Shower technology

# Innovations for extraordinary shower pleasure

Showering is much more than just a question of hygiene. With Hansgrohe shower systems, it becomes an experience. Our overhead showers and shower systems combine design excellence with technologies that make our products the most innovative on the market. This brochure offers you all the relevant information for the planning and installation of the shower systems presented here.

## Ground-breaking Hansgrohe shower technologies – greater shower pleasure for your customers




**AirPower:** Our AIR technology mixes water with air, just as in nature. This not only creates the effect of a rain shower, but also reduces water consumption. At the same time, the volume of water in the shower seems much greater.



**QuickClean:** No more limescale or other deposits: our QuickClean surfaces can be cleaned with a simple rubbing motion. This prevents the jets from clogging up, and keeps the showers looking like new – for years to come.



**ComfortZone:** Our trend-setting ergonomic concept permits comfortable operation of the mixers, while protecting against extreme temperatures.



**XXL Performance:** Hansgrohe started the trend towards larger showers. We were one of the first manufacturers to introduce extra-large showers with excellent spray quality that offer extraordinary shower pleasure.



**EcoSmart:** The innovative combination of flow limitation, special spray jets, and the mixture of water and air reduces the water consumption of showers and basin mixers.  
**In this brochure, EcoSmart versions are marked with a drop symbol.**



## Shower pleasure has many faces

---

The Hansgrohe world of shower systems offers the perfect solution for each of your customers: from Showerpipes as a simple exposed installation (ideal for quick bathroom renovations) to overhead showers with one, two or three spray modes or an extra-large spray surface, all the way to high-end installations with additional invigorating side showers.

In this brochure you will find all the necessary technical information for working with shower systems: measurements, flow rate charts, planning and installation instructions as well as useful tips from our technicians.




1-spray shower systems; Example: Raindance® S 240 AIR overhead shower with Raindance® S 100 AIR 3jet hand shower, page 8–13



2-spray shower systems; Example: Raindance® E 420 AIR 2jet overhead shower with PuraVida® 150 3jet hand shower, page 14–17





Product variations



3-spray shower systems; Example: Raindance® Rainfall® 3jet overhead shower with Raindance® S 100 AIR 3jet hand shower, page 18–23



3-spray shower systems; Example: Raindance® Rainmaker® AIR overhead shower with Raindance® S 150 AIR 3jet hand shower, page 24–31



3-spray shower systems with side showers; Example: Raindance® Rainmaker® with Raindance® S 150 AIR 3jet hand shower, page 32–33



Shower systems for exposed installation, ideal for renovation purposes; Example: Raindance® Showerpipe 240, page 34–45















## System 1: 1-spray overhead showers

**Like showering in rain:** Raindance AIR plate overhead showers release a particularly lavish spray of water that feels just like a natural rain shower. They are available in different versions: as a super-slim model, in the Style version or with a more elaborate appearance in the Classic version. The 1-spray shower range is available in diameters of 180 to 350 mm for ceiling or wall installation. The rectangular E-models are available up to a width of 420 mm. A truly royal experience is promised by the Raindance AIR Royale. Made from solid metal and crafted by expert hands, it offers you an incredible diameter of 350 mm.


**Raindance® S 180 AIR** overhead shower




**Raindance® S 240 AIR** overhead shower



**Raindance® S 300 AIR** overhead shower



**Raindance® Royale S 350 AIR** overhead shower




# Raindance® S 240 overhead shower

## Flow rate chart

# 27474000

Raindance AIR Ø 240 mm overhead shower




### Key

overhead shower

## Flow rate chart

# 28504000

Raindance S 100 AIR 3jet hand shower



### Key


- ① Rain AIR
- ② Mix AIR
- ③ Whirl AIR

Function guaranteed from • onwards.

## Components

- Ⓐ 1x # 27474000 Raindance AIR Ø 240 mm overhead shower
- Ⓑ 1x # 15721000 Ecostat S thermostat with shut-off/diverter valve
- 1x # 01800180 iBox universal basic set
- Ⓒ 1x # 28504000 Raindance S 100 AIR 3jet hand shower
- 1x # 28331000 Porter S shower support
- 1x # 28276000 Isiflex shower hose 1.60 m
- Ⓓ 1x # 27453000 Fixfit E hose connection
- Ⓔ 1x # 60056000 Staro 90 waste set

Products Ⓐ and Ⓒ are also available in an EcoSmart version.








# Raindance® Royale 350 overhead shower

## Flow rate chart

# 28420000

Raindance Royale AIR overhead shower




### Key

overhead shower

## Flow rate chart

# 27893000

Raindance Unica'S Set 0,90 m




### Key

- ① Rain AIR
- ② Mix AIR
- ③ Whirl AIR

Function guaranteed from • onwards.

## Components

- Ⓐ 1x # 2842000 Raindance Royale AIR Ø 350 mm overhead shower
  - Ⓑ 1x # 27418000 Ceiling connector 100 mm
  - Ⓒ 1x # 27893000 Raindance Unica'S Set 0.90 m
  - Ⓓ 1x # 15932000 Trio S shut-off/diverter valve
  - 1x # 15981180 Trio basic set
  - Ⓔ 1x # 15715000 Ecostat S Highflow thermostat
  - 1x # 01800180 iBox universal basic set
  - Ⓕ 1x # 27453000 Fixfit S hose connection
  - Ⓖ 1x # 60067000 Raindrain 90 XXL waste set
- Product Ⓑ is also available in an EcoSmart version.













## System 2: 2-spray overhead showers

**Elegance and ergonomics:** The Rainfall 180 2jet and Raindance E 420 2jet overhead showers with two spray modes are ideal components for a sophisticated shower system. The compact Rainfall 180 2jet overhead shower exudes timeless elegance, while the width of the Raindance E 420 2jet overhead shower was designed to completely cascade around your shoulders. Both overhead showers offer the choice between the lavish Rain AIR function and the invigorating water fall of the Rainflow flood jet.

Raindance® Rainfall® 180 2jet overhead shower



Raindance® E 420 AIR 2jet overhead shower






# Raindance® Rainfall® 180 2jet overhead shower

## Flow rate chart

# 28433000

Raindance Rainfall overhead shower




### Key

- ① Rain AIR
- ② Rainflow
- ③ Rain AIR + Rainflow

## Flow rate chart

# 28504000

Raindance S 100 AIR 3jet hand shower



### Key


- ① Rain AIR
- ② Mix AIR
- ③ Whirl AIR

Function guaranteed from • onwards.

## Components

- Ⓐ 1x # 28433000 Raindance Rainfall 180 2jet overhead shower
- 1x # 01800180 iBox universal basic set
- Ⓑ 1x # 28504000 Raindance S 100 AIR 3jet hand shower
- 1x # 28331000 Porter S shower support
- 1x # 28276000 Isiflex shower hose 1.60 m
- Ⓒ 1x # 15932000 Trio S shut-off/diverter valve
- 1x # 15981180 Trio basic set
- Ⓓ 1x # 15715000 Ecostat S Highflow thermostat
- 1x # 01800180 iBox universal basic set
- Ⓔ 1x # 15972000 Shut-off valve S
- 1x # 15974180 Shut-off valve basic set
- Ⓕ 1x # 27453000 Fixfit S hose connection
- Ⓖ 1x # 60067000 Raindrain 90 XXL waste set

Product Ⓑ is also available in an EcoSmart version.






# Raindance® E 420 AIR 2jet overhead shower

## Flow rate chart

# 27373000

Raindance E 420 AIR 2jet overhead shower




### Key

- ① Rain AIR XL
- ② Rainflow

## Flow rate chart

# 28557000

PuraVida 150 3jet hand shower



### Key


- ① Rain AIR
- ② Mix AIR
- ③ Caresse AIR

Function guaranteed from • onwards.

## Components

- Ⓐ 1x # 27373000 Raindance E 420 AIR 2jet overhead shower  
1x # 01800180 iBox universal basic set
- Ⓑ 1x # 28557000 PuraVida 150 3jet hand shower  
1x # 28331000 Porter S shower support  
1x # 28276000 Isiflex shower hose 1.60 m
- Ⓒ 1x # 15777000 iControl shut-off/diverter valve for PuraVida  
1x # 01800180 iBox universal basic set
- Ⓓ 1x # 27414000 Fixfit hose connection for PuraVida
- Ⓔ 1x # 15772000 Highflow thermostat for PuraVida  
1x # 01800180 iBox universal basic set
- Ⓕ 1x # 60067000 Raindrain 90 XXL waste set

Product Ⓑ is also available in an EcoSmart version.









## System 3: 3-spray overhead showers

**Variety for body and soul:** From here on, shower pleasure becomes pure luxury. Our shower systems with 3-spray overhead showers captivate with their unique appearance, all-round shower pleasure and easy operation. The Raindance Rainfall is installed flush with the wall and reaches well into the room. It offers great experience with three spray modes (Rain AIR, Whirl AIR and Rainflow). The Raindance Rainmaker represents showering in even larger dimensions: it is installed flush with the ceiling, creating a completely new and extremely generous sense of space. It is available both in a rectangular and a round version and can also be equipped with lighting.



Raindance® Rainfall® 3jet overhead shower



Raindance® Rainmaker® AIR overhead shower



Raindance® Rainmaker® AIR overhead shower






# Raindance® Rainfall® overhead shower iControl® mobile

## Flow rate chart

# 28411000

Raindance Rainfall overhead shower




### Key

- ① Rain AIR
- ② Whirl AIR
- ③ Rainflow

## Flow rate chart

# 28504000

Raindance S 100 AIR 3jet hand shower




### Key

- ① Rain AIR
- ② Mix AIR
- ③ Whirl AIR

Function guaranteed from • onwards.

## Components

- |                                                                                                                                                                                                         |                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Ⓐ 1x # 28411000 Raindance Rainfall overhead shower</li> <li>1x # 01800180 iBox universal basic set</li> </ul>                                                    | <ul style="list-style-type: none"> <li>Ⓓ 1x # 15715000 Ecostat S Highflow thermostat</li> <li>1x # 01800180 iBox universal basic set</li> </ul> |
| <ul style="list-style-type: none"> <li>Ⓑ 1x # 28504000 Raindance S 100 AIR 3jet hand shower</li> <li>1x # 28331000 Porter S shower support</li> <li>1x # 28276000 Isiflex shower hose 1.60 m</li> </ul> | <ul style="list-style-type: none"> <li>Ⓔ 1x # 15972000 Shut-off valve S</li> <li>1x # 15974180 Shut-off valve basic set</li> </ul>              |
| <ul style="list-style-type: none"> <li>Ⓒ 1x # 15942000 iControl mobile shut-off/diverter valve</li> <li>1x # 15941180 iControl mobile basic set</li> </ul>                                              | <ul style="list-style-type: none"> <li>Ⓕ 1x # 27453000 Fixfit S hose connection</li> <li>Ⓖ 1x # 60067000 Raindrain 90 XXL waste set</li> </ul>  |
- Product Ⓑ is also available in an EcoSmart version.






# Raindance® Rainfall® overhead shower

## Flow rate chart

# 28411000

Raindance Rainfall overhead shower




### Key

- ① Rain AIR
- ② Whirl AIR
- ③ Rainflow

## Flow rate chart

# 28504000

Raindance S 100 AIR 3jet hand shower



### Key


- ① Rain AIR
- ② Mix AIR
- ③ Whirl AIR

Function guaranteed from • onwards.

## Components

- |                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Ⓐ 1x # 28411000 Raindance Rainfall overhead shower</li> <li>1x # 01800180 iBox universal basic set</li> <li>Ⓑ 1x # 28504000 Raindance S 100 AIR 3jet hand shower</li> <li>1x # 28331000 Porter S shower support</li> <li>1x # 28276000 Isiflex shower hose 1.60 m</li> <li>Ⓒ 1x # 15932000 Quattro S diverter valve</li> <li>1x # 15930180 Quattro basic set</li> </ul> | <ul style="list-style-type: none"> <li>Ⓓ 1x # 15972000 Shut-off valve S</li> <li>1x # 15970180 Shut-off valve basic set</li> <li>Ⓔ 1x # 15715000 Ecostat S Highflow thermostat</li> <li>1x # 01800180 iBox universal basic set</li> <li>Ⓕ 1x # 38882000 Fixfit Stop hose connection</li> <li>Ⓖ 1x # 60067000 Raindrain 90 XXL waste set</li> </ul> |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Product Ⓑ is also available in an EcoSmart version.



# Raindance® Rainfall®

## Planning and installation instructions

### Wall installation

#### 1. iBox universal as a basic set

The versatile iBox universal concealed installation unit is also used with the overhead shower, providing a rapid and professional installation of the Raindance Rainfall. Considering the exceptional length and weight of this overhead shower, the iBox universal ensures that the Raindance Rainfall is securely mounted and sits perfectly on the wall (product not included in delivery).

**Attention:** The net weight of the shower without water is 12 kg. Please ensure sufficient wall reinforcement at point of installation!

To direct the water coming from the three G ½ feed pipes to the three shower functions, a fixing aid is needed at the shower – sitting directly on the iBox universal. This solid brass function block integrates the three brass pipes which ensure the stable mounting of the shower.

Another brass pipe is screwed into the fourth (upward-pointing) opening of the iBox universal and attached to the wall with an ordinary pipe clamp, providing additional stability. The middle feed pipe is also secured with a clamp.

The pre-assembled overhead shower panel, including the pre-attached wall escutcheon, is placed over the three shower arms and screwed on at the sides. Finished!

**Attention:** The shower has to be installed, rinsed and checked in compliance with the applicable regulations in order to guarantee a proper shower function!

### Plumbing installation

#### 2. Hot water supply

The dimensions of the shower set-up must be individually established according to personal shower preferences, frequency of usage and the number of desired shower functions. Recommended operating pressure: 3 bar pressure. Hot water temperature: max. 60°C. Recommendation: the storage tank should hold at least 300 litres.

**Note:** This product cannot be used in combination with continuous flow water heaters. Large differences in pressure between the cold and hot water outlets must be balanced.

#### 3. Feed pipes

iBox universal: 2 x G ¾ (hot/cold)

Rainfall: 3 x G ½ (mixed water)

**4. Concealed thermostat** on iBox universal base # 15715000 concealed thermostat with increased flow capacity and cylindrical handle not included in delivery. Flow rate 58 l/min at 3 bar.

# 01800180 iBox universal not included in delivery!

Further options for finish sets (see Product Overview Basic and Finish Sets) and custom-made surfaces are available on request.


#### 5. Shut-off valves G ¾ with cylindrical handle

Not included in delivery!

# 15970180 Basic Set G ¾ (spindle) for concealed installation, flow rate 130 l/min at 3 bar

# 15972000 Finish Set Shut-off valve





3-spray overhead showers

## 6. Quattro Diverter Valve G<sup>3/4</sup> with cylindrical handle

Not included in delivery!

For the easy operation of all three functions:

# 15930180 Basic Set G<sup>3/4</sup> with ceramic discs for

concealed installation, flow rate 65 l/min at 3 bar

# 15932000 Quattro diverter finish set

## 7. Shut-off valve G<sup>1/2</sup> with cylindrical handle

Shut-off valve for hand shower

# 38882000 Hose connector Fixfit Stop

## 8. Drain

Floor drain (without shower tray):

Raindrain 90 XXL


Drain capacity 51 l/min (damming height 15 mm)  
complies with DIN 1247 1-3.



Raindrain 90 XXL Complete Set

# 60067000

**Attention:** The drain capacity must be greater  
than 50 l/min





# Product description and technical data

## Raindance Rainfall overhead shower # 28411000

Includes:

Pre-assembled overhead shower panel with three shower functions for wall mounting

1 x Raindance Rainfall overhead shower  
Including wall escutcheon

1 x Function block with three shower arms  
(for mounting on the iBox universal)





- chromed brass housing and spray disc
- chromed metal wall escutcheon

240 mm Raindance overhead shower with AIR function for soft, voluminous rain drops and tried-and-tested QuickClean cleaning function.

Wide flood jet (hot or cold water) with high flow capacity for a completely new, natural shower experience.

Three spray modes:

- 1** Rain AIR: Large overhead shower 240 mm
- 2** Whirl AIR: 4 nozzles with rotating massage jets
- 3** Rainflow: Wide flood jet










# Installation

## Installation

In your planning, please consider the size and layout of the shower cubicle and the spray angles of the individual spray modes.




# Raindance® Rainmaker® round overhead shower

## Flow rate chart

# 28403000


Raindance Rainmaker overhead shower



## Flow rate chart

# 28504000


Raindance S 100 AIR 3jet hand shower



Function guaranteed from • onwards.

## Components

- |                                                                                                                                                          |                                                                                                      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <p>Ⓐ 1x # 28403000 Raindance Rainmaker Ø 600 mm overhead shower</p> <p>1x # 28412180 Raindance Rainmaker basic set</p>                                   | <p>Ⓓ 1x # 15972000 Shut-off valve S</p> <p>1x # 15970180 Shut-off valve basic set</p>                |
| <p>Ⓑ 1x # 28504000 Raindance S 100 AIR 3jet hand shower</p> <p>1x # 28331000 Porter S shower support</p> <p>1x # 28276000 Isiflex shower hose 1.60 m</p> | <p>Ⓔ 1x # 15715000 Ecostat S Highflow thermostat</p> <p>1x # 01800180 iBox universal basic set</p>   |
| <p>Ⓒ 1x # 15932000 Quattro S diverter valve</p> <p>1x # 15930180 Quattro basic set</p>                                                                   | <p>Ⓕ 1x # 38882000 Fixfit Stop hose connection</p> <p>Ⓖ 1x # 60067000 Raindrain 90 XXL waste set</p> |
- Product Ⓑ is also available in an EcoSmart version.






# Raindance® Rainmaker® rectangular overhead shower



## Flow rate chart

# 28417000

Raindance Rainmaker overhead shower




### Key

- ① Rain AIR XL
- ② Rain AIR XXL
- ③ Whirl AIR

## Flow rate chart

# 27638000

Raindance Unica'S Set 1,50 m



### Key


- ① Rain AIR
- ② Mix AIR
- ③ Whirl AIR

Function guaranteed from • onwards.

## Components

- Ⓐ 1x # 28417000 Raindance Rainmaker 680 mm x 460 mm overhead shower
- Ⓑ 1x # 15932000 Quattro S diverter valve
- Ⓒ 1x # 15932000 Trio S shut-off/diverter valve
- Ⓓ 1x # 15715000 Ecostat S Highflow thermostat
- Ⓔ 1x # 01800180 iBox universal basic set
- Ⓕ 1x # 27453000 Fixfit S hose connection
- Ⓖ 1x # 27638000 Raindance Unica'S Set 1.50 m
- Ⓗ 1x # 60067000 Raindrain 90 XXL waste set

Product Ⓔ is also available in an EcoSmart version.



# Raindance® Rainmaker®

## Planning and installation instructions

### Ceiling construction

#### 1. Suspended ceiling

To install the Rainmaker, you need to install a suspended ceiling (made of plaster board for example) yielding a gap of at least 6 cm. Stretched ceilings are an ideal alternative to plaster board sheets (see Installation of plaster board sheets, Installation with stretched ceilings).

The Rainmaker cannot be incorporated into concrete framework installation and sealed afterwards. To install the housing into concrete ceilings and in a plaster board ceiling, a circular opening of 590 mm is recommended, leaving a 5.5 mm overhang. It is possible to install the Rainmaker flush with the ceiling, leaving a circular seam of 7 mm to allow for the installation of cover sheets on the sides.

The Rainmaker's own weight, without water, is around 12 kg.

**Attention:** Not suitable for direct installation in open spaces adjacent to flammable surfaces.

#### 2. Basic set/Installation instructions

The basic set needs to be ordered in advance and is designed as an installation aid. It doesn't contain any expensive components and can therefore be installed during the early phases of construction. The basic set is required to install the actual finish set. It comprises mainly a polystyrene housing with a spray disc template to enable exact positioning of the Rainmaker in the room and fixing of the three connecting hoses. Thanks to the supplied plugs, it is possible to do a pressure test at this early stage. All attachment screws for the basic and finish set are also included. Before the final installation, the polystyrene finish set dummy is broken up and removed.



### Plumbing installation

#### 3. Hot water supply

The capacity of the shower set-up must be individually established according to personal shower preferences, frequency of usage and the number of desired shower functions. Operating pressure at the thermostat: max. 1 MPa. Recommended operating pressure: 3 bar pressure. Hot water temperature: max. 60 °C. Recommendation for the storage tank: the storage tank should hold at least 300 litres.

**Note:** This product cannot be used in combination with continuous flow water heaters. Large differences in pressure between the cold and hot water outlets have to be balanced.

#### 4. Supply lines

iBox universal: 2 x G 3/4 (hot/cold)

Rainmaker: 3 x G 1/2 (mixed water)

**5. Concealed thermostat** on iBox universal base # 15715000 concealed thermostat with increased flow capacity and cylindrical handle included in delivery. Flow rate 58 l/min at 3 bar.

# 01800180 iBox universal not included in delivery!

Further options for finish sets (see Product Overview Basic and Finish Sets) and custom-made surfaces are available on request.

#### 6. Shut-off valve G 3/4 with cylindrical handle

Not included in delivery!

# 15970180 Basic Set G 3/4 (spindle) for concealed installation, flow rate 130 l/min at 3 bar

# 15972000 Finish Set Shut-off valve

#### 7. Quattro Diverter Valve G 3/4 with cylindrical handle


Not included in delivery!

For the easy operation of all three functions:

# 15930180 Basic Set G 3/4 with ceramic

discs for concealed installation, flow rate 65 l/min at 3 bar

# 15932000 Quattro diverter finish set



3-spray overhead showers

### 8. Shut-off Valve G 1/2 with cylindrical handle

Shut-off valve for hand shower

# 38882000 Hose connector Fixfit Stop

## Waste Technology

### 9. Drain

Floor drain (without shower tray)


Drain for shower tray: Raindrain 90 XXL

Drain capacity 51 l/min (15 mm damming height),  
complies with DIN 1247 1-3.



Raindrain 90 XXL Complete Set  
# 60067000

**Attention:** The drain capacity must be greater than 50 l/min



## Electrical installation

### 10. Feed line (2 x 1,5 mm<sup>2</sup>)

Electrical junction box included in the basic set Note: Make sure ducting is laid for the power supply (lighting). Equipotential bonding is not required.


**Attention:** Connection of electricity must be carried out by an electrician! Power supply 230V/N/PE/50Hz (length 0.3 m). Protection must be provided via a residual current-operated protective device (RCD/FI) with a maximum residual operating current of 30 mA.

### 11. Light switch

Must be installed outside the shower area or connected with the ceiling light (outside protection area two according to WRC regulations).

### 12. Transformer

Secondary output voltage 12V/35-80 VA,  
dimensions 110 mm x 21 mm x 45 mm.





# Product description and technical data

## Rainmaker Basic set # 28412180

### Contents:




- 1x polystyrene housing with template
- 1x electrical junction box with connection accessories
- 2x connecting hoses 800 mm, G 1/2  
(1 straight connection, 1 elbow connection)
- 1x connecting hose, 800 mm, G 1/2  
(2 straight connections)

### Mounting material

(included in basic set)

The supplied plugs are suitable for concrete ceilings. For other building materials suitable mounting elements must be used. The plugs supplied are

- 4x washers
- 4x stainless steel nuts M 8
- 4x plastic plugs Ø 10 mm
- 4x hanger bolts M 8 x 100 mm  
(for installation heights > 10 cm longer hanger bolts will need to be purchased separately)
- 4x stainless steel screws
- 4x plastic plugs
- 4x washers Ø 6 x 22 mm
- 1x belt strap (for secure installation)





# Installation

## Raindance Rainmaker Finish set without lighting # 28403000

Content:



Concealed high-flow thermostat on iBox universal base

# 15715000

Pre-assembled overhead shower system with three available functions:

- 1) central overhead shower 264 x 282 mm
- 2) full body shower 528 x 282 mm
- 3) massage jets 264 mm

358 jet elliptical spray disc with the proven elastic silicon nipple based QuickClean de-scaling function. Same look as # 28404000 but without glass light elements.



## Raindance Rainmaker Finish set with lighting # 28404000

Construction and function as # 28403000


in addition 4 x 20 halogen lamps, type 50020 Osram

Ministar, transformer with secondary output voltage

12 V/35-80 VA, 110 mm x 21 mm x 45 mm,

concealed high-flow thermostat on iBox universal base

# 15715000



## Raindance Rainmaker housing

For clearer presentation of the details the housing is here shown in grey; in the original it is black.



## 3-spray overhead showers with side showers


---

**Water from all directions:** When the entire Hansgrohe shower family consisting of hand shower, overhead shower and side showers are brought together, the result is a system that creates a total sense of wellbeing.



### **Rain AIR**

Air is drawn in through the entire spray disc and mixed together with the inflowing water. As a result, the drops become larger, lighter and softer. A natural rain shower is created.



### **Rain AIR XXL**

The Rain AIR function in maximum size: a down-pour of water envelopes the entire body.



### **Whirl AIR**

This function also mixes water with air. The air is compressed into a very small space, which accelerates the outflowing massage jets. The result is a powerful massage with a rotating jet.






# 3-spray overhead shower Raindance® Rainmaker® with side shower

## Flow rate chart

# 28403000

Raindance Rainmaker overhead shower




### Key

- ① Rain AIR XL
- ② Rain AIR XXL
- ③ Whirl AIR

## Flow rate chart\*

# 28477000

Raindance AIR side shower



### Key


- ① 1 Body shower
- ② 3 Body showers
- ③ 6 Body showers

Function guaranteed from • onwards.

\* Flow rate chart # 27638000 Raindance Unica'S Set see page 27.

## Components

- Ⓐ 1x # 28403000 Raindance Rainmaker Ø 600 mm overhead shower
  - Ⓑ 1x # 15955000 iControl manual shut-off/diverter valve
  - Ⓒ 1x # 15715000 Ecostat S Highflow thermostat
  - Ⓓ 1x # 15932000 Trio S shut-off/diverter valve
  - 1x # 15981180 Trio basic set
  - Ⓔ 1x # 27453000 Fixfit S hose connection
  - Ⓕ 1x # 27638000 Raindance Unica'S Set 1.50 m
  - Ⓖ 6x # 28477000 Raindance AIR side shower
  - Ⓗ 1x # 60067000 Raindrain 90 XXL waste set
- Product Ⓔ is also available in an EcoSmart version.








## System 4: Showerpipe

**The simple way to intense shower pleasure:** Hansgrohe Showerpipes mark a new trend in the modern bathroom: sleek, aesthetically designed overhead showers that produce a warm, comforting shower rain. Whether it be a new installation or a bathroom upgrade, whether it be Raindance or Croma 100 – all Showerpipes are quickly and easily installed. Since they are installed in front of the wall, they can easily be upgraded at any time. No need to open up the walls.

### Raindance® Select 360 Showerpipe




# Raindance® Select 360 Showerpipe

## Flow rate chart

# 27112,-000,-400


Raindance Select 360 Showerpipe



### Key


- ① hand shower
- ② overhead shower

Function guaranteed from • onwards.



## Components

- Ⓐ 1x # 27112,-000,-400  
Raindance Select 360  
Showerpipe
- Ⓑ 1x # 60056000 Staro 90  
waste set








# Raindance® E 420 2jet Showerpipe

## Flow rate chart

# 27149000


Raindance E 420 2jet Showerpipe



### Key


- ① hand shower
- ② overhead shower
- ③ flood shower

Function guaranteed from • onwards.



## Components

- Ⓐ 1x # 27149000  
Raindance E 420 2jet  
Showerpipe
- Ⓑ 1x # 60056000 Staro 90  
waste set




# Raindance® 240 Showerpipe for concealed installation

## Flow rate chart

# 27145000


Raindance 240 Showerpipe for concealed installation



### Key


- ① overhead shower
- ② hand shower
- ③ overhead shower + hand shower

Function guaranteed from • onwards.



## Components

- Ⓐ 1x # 27145000  
Raindance 240 Showerpipe  
for concealed installation  
1x # 01800180 iBox universal  
basic set
- Ⓑ 1x # 60056000 Staro 90  
waste set






# Raindance® Connect 240 Showerpipe

## Flow rate chart

# 27421000



Raindance Connect 240 Showerpipe



## Key

- ① overhead shower
- ② hand shower

Function guaranteed from • onwards.



## Components


- Ⓐ 1x # 27421000  
Raindance Connect 240  
Showerpipe  
Easy to mount on any existing  
mixer or shower connection.
- Ⓑ 1x # 13116000  
EcoStat Comfort Shower
- Ⓒ 1x # 60056000 Staro 90  
waste set

# Raindance® Select 300 Showerpipe

## Flow rate chart

# 27114000

Raindance Select 300 Showerpipe




Q = l/min 0 3 6 9 12 15 18 21 24 27 30  
 Q = l/sec 0 0,1 0,2 0,3 0,4 0,5

### Key

- ① overhead shower
- ② hand shower

Function guaranteed from • onwards.



Ceiling

2245 mm ..... (A)

1100 mm .....

G 1/2

G 1/2

0 mm .....  
Floor

(B)

## Components

- (A) 1x # 27114000  
Raindance Select 300  
Showerpipe
- (B) 1x # 60056000 Staro 90  
waste set




# Raindance® Select 240 Showerpipe for the bath tub



## Flow rate chart

# 27117000


Raindance Select 240 Showerpipe for the bath tub



### Key


- ① overhead shower
- ② hand shower
- ③ bath filler

Function guaranteed from • onwards.



## Components

- Ⓐ 1x # 27117000  
Raindance Select 240  
Showerpipe for the  
bath tub
- Ⓑ 1x # 58143000 Flexaplus  
Waste and overflow




# Croma® 220 Showerpipe

## Flow rate chart

# 27185000


Croma 220 Showerpipe



### Key

- ① overhead shower
- ② hand shower


Function guaranteed from • onwards.



## Components

- Ⓐ 1x # 27185000  
Croma 220 Showerpipe
- Ⓑ 1x # 60056000 Staro 90  
waste set

Product Ⓐ is also available  
in an EcoSmart version  
# 27188000






# Croma® 160 Showerpipe

## Flow rate chart

# 27135000

Croma 160 Showerpipe




Q = l/min 0 3 6 9 12 15 18 21 24 27 30  
 Q = l/sec 0 0,1 0,2 0,3 0,4 0,5

### Key


- ① overhead shower
- ② hand shower

Function guaranteed from • onwards.



## Components


- Ⓐ 1x # 27135000  
Croma 160 Showerpipe
- Ⓑ 1x # 60056000 Staro 90  
waste set




# Flexible in height

Regardless of the height of the room and the water connections, round tube Showerpipes can always be placed in the optimum position. The round tube is quickly and easily cut to the right length, which means that individual customer requirements can be met.

Room height A



Room height B







## Versatile positioning

The swivelling head makes the Showerpipes extremely versatile – perfect for use in any bath or shower situation.


### **Bath:**

Showerpipes can easily be installed on the front or long side of the bath, according to the position of the water connections. The shower head can also be individually aligned.


### **Shower:**

Often, the existing water connections are not positioned in the middle of a shower area. Thanks to the swivelling arm, the shower head can still be placed in the middle of the shower after installation.

**Bath installation**



**Shower installation**





# Hansgrohe iBox® universal – Flexibility that benefits everyone


In the world of installation, the iBox universal has long been a standard for concealed fittings. Since its introduction, it has been the one and only basic set for all Hansgrohe and Axor standard thermostats. With the iBox universal, Hansgrohe offers an extremely flexible concealed installation system which allows a basic set built into the wall to be connected to various finish sets for mixers and showers. It can be connected to several different attachments in a variety of ways.



## Possible iBox® universal combinations




1. Single lever bath mixer
2. Single lever bath mixer/safety combination
3. Single lever shower mixer
4. Ecostat® S thermostat
5. Ecostat® S Highflow thermostat
6. Metris thermostat shut-off valve
7. Ecostat® S thermostat shut-off & diverter valve
8. Combined Bath filler/Porter unit
9. iControl® manual
10. iControl® mobile
11. Raindance® Rainfall®
12. Raindance® E 420 2jet overhead
13. Raindance® Showerpipe 240




iBox® universal

# The many benefits of the iBox® universal




## Rotationally symmetrical installation

- Symmetrical structure; all connections are equal.
- It is important that the cold water is connected on the right and the hot water on the left.
- When used as a bath mixer, the lower outflow takes priority.
- When the iBox universal is used as a shower mixer, either the upper or lower outflow can be connected.




## Safe and economical

- The basic set contains just the connection block. The valuable fitting aid is delivered and installed later, together with the finish set.
- Prevents problems like theft, dirt and frost occurring during the building phase; expensive warehousing becomes unnecessary.




## Multiple installation options

- Coordinated with all current installation systems and all types of connections and fittings.
- Patented flexible adjustment ring.
- Mounting options at two levels and G<sup>3/4</sup> connections for universal installation possibilities.
- Also suitable for thicker walls and dry wall installations as well as for pre-fabricated housing systems.




## Integrated safety combination

- When installing a concealed single lever bath mixer with integrated safety combination – together with an Exafill bath filler with waste and overflow set – an external pipe interrupter becomes unnecessary. This reduces installation costs as well as the number of functional parts inside the wall.




## Excellent protection against humidity

- Seals on all four connections and the supporting collar which seals against splashing water perfectly protect the wall against moisture coming from any direction.




## Solutions for walls

- If the iBox universal sits too deep in the wall, the basic unit extension is fitted between the connector and the function block.
- The iBox universal standard basic set has been made flatter and is now even better suited for walls with limited installation depths.




## Low noise level

- The brass body rests on seals, preventing sound from the water-conducting parts from being transferred through the wall.
- The supporting collar is screwed to the iBox universal housing and not to the function block, which prevents sound from being transferred through to the tiles.




## Collar extension

- Thanks to the extension, even limited installation depths are no longer a problem.
- The extension collar makes it possible to install the iBox universal despite the lack of depth.



## Flushing

- The flushing block supplied with the iBox universal can be mounted in different positions. This makes it easy at the wall during installation.



## Compatible with smaller escutcheon diameters

- The operating handles and escutcheons of the various mixer series are becoming more and more minimalist.
- The iBox universal is compatible with concealed mixers with 170 mm and a smaller 150 mm finishing sets.

# Ideal for all Axor and Hansgrohe basic and finish sets

---

With the iBox universal, Hansgrohe offers a solution that covers all concealed installations using Hansgrohe and Axor mixers. All shut-off and diverter valves and all thermostats from both brands can be easily combined with the iBox.

It is suitable for six different functional solutions (G 1/2 and G 3/4 installations). For the Raindance, Rainmaker, Rainfall and Royale overhead showers you require the matching concealed installation thermostat with increased flow capacity on the iBox universal base. Thanks to the iBox universal technology all options are left open – even after the construction phase. The valuable fitting aid can be delivered and installed afterwards, together with the finish set.

## Shut-off valves

---



Spindle basic set, G 3/4  
# 15970180  
Spindle basic set, G 1/2  
# 15973180  
Ceramic basic set, G 1/2  
# 15974180

## Shut-off and diverter valves

---



Trio 2 way diverter basic set  
# 15981180  
Quattro 3 way diverter basic set  
# 15930180

## iBox® universal


---



**iBox® universal**  
Basic set for concealed installation thermostat  
# 01800180  
Extension 25 mm  
# 13595000  
Collar extension  
170 mm # 13596000  
Collar Extension  
150 mm # 13597000









Basic and finish sets

# Possible combinations


## Thermostats



**Ecostat® S**  
 # 15711000  
 iBox universal basic set  
 # 01800180  
 Please note this product requires a separate on/off control




**Ecostat® S**  
 with integrated shut-off valve  
 # 15701000  
 iBox universal basic set  
 # 01800180




**Ecostat® S**  
 with integrated shut-off and diverter valve  
 # 15721000  
 iBox universal basic set  
 # 01800180

## Shut-off and diverter valves



**iControl® mobile**  
 electronic shut-off and diverter valve  
 # 15945000  
 iControl mobile basic set  
 # 15941180




**iControl® S**  
 with integrated shut-off and diverter valve  
 # 15955000  
 iBox universal basic set  
 # 01800180  
 Please note this product requires a separate high flow thermostat




## Shut-off valves

**Shut-off valve S**  
 # 15972000  
 Spindle basic set, G 3/4  
 # 15970180  
 Spindle basic set, G 1/2  
 # 15973180  
 Ceramic basic set, G 1/2  
 # 15974180
























**Trio®**  
 2 way diverter and shut-off valve  
 Finish set S  
 # 15932000  
 Trio basic set  
 # 15981180




**Quattro®**  
 3 way diverter valve  
 Finish set S  
 # 15932000  
 Quattro basic set  
 # 15930180

# Hansgrohe finish sets

	<b>Hansgrohe PuraVida®</b>	<b>Hansgrohe E</b>	<b>Hansgrohe S</b>	<b>Hansgrohe Classic</b>
<b>Trio/Quattro</b>	 # 15937400	 # 15931000	 # 15932000	 # 15934000
<b>Shut-off valve</b>	 # 15978400	 # 15971000	 # 15972000	 # 15961000
<b>Thermostat</b>	 # 15772400	 # 15710000	 # 15715000	 # 15754000
<b>Shut-off and diverter valve</b>	<b>Hansgrohe PuraVida®</b>	<b>Hansgrohe E</b>	<b>Hansgrohe S</b>	
<b>Shut-off and diverter valve</b>	 # 15777400	 # 15958000	 # 15955000	
<b>Thermostat</b>	 # 15772400	 # 15710000	 # 15715000	
<b>Thermostat</b>	<b>Hansgrohe PuraVida®</b>	<b>Hansgrohe E</b>	<b>Hansgrohe S</b>	
<b>Thermostat</b>	 with integrated shut-off and diverter valve # 15771000 with integrated shut-off valve # 15775000	 with integrated shut-off and diverter valve # 15720000 with integrated shut-off valve # 15700000	 with integrated shut-off and diverter valve # 15721000 with integrated shut-off valve # 15701000	

Please refer to the Hansgrohe price list or the Hansgrohe catalogue for the different surface finish options.



# Axor finish sets

## Axor Starck

## Axor Starck X

## Axor Citterio

Trio/Quattro  
# 10930000



# 10934000



Cross head handle  
# 39925000



Lever handle  
# 39920000

Shut-off valve  
# 10970000



# 10974000



Cross head handle  
# 39965000



Lever handle  
# 39960000

Thermostat  
# 10715000



# 10717000



Cross head handle  
# 39716000



Lever handle  
# 39711000

## Axor Citterio M

## Axor Urquiola

## Axor Massaud

## Axor Bouroullec

Trio/Quattro  
# 34920000



# 11925000



# 18730000



# 19981000

Shut-off valve  
Lever handle  
# 34960000



Star-shaped handle  
# 34980000



# 11960000



# 18770000



# 19971000

Thermostat  
# 34716000



# 11731000



# 18741000



# 19702000

## Axor Uno<sup>2</sup>

## Axor Carlton

## Axor Montreux

Trio/Quattro  
# 38933000



Cross head handle  
# 17925000



Lever handle  
# 17920000



# 16830000

Shut-off valve  
# 38976000



Cross head handle  
# 17965000



Lever handle  
# 17960000



# 16871000

Thermostat  
# 38715000



Cross head handle  
# 17716000




Lever handle  
# 17712000



# 16815000



# RainBrain® – the mastermind in the shower



RainBrain is another genuine innovation from Hansgrohe: a control for shower programmes, operated intuitively via touch-screen. For example, you can activate the different functions at the touch of a button, and then focus on nothing else except enjoying your shower. And it's not only showering that becomes more comfortable – you can even send music from your MP3 player to your RainBrain.





## Planning and installation instructions



### 1. Hot and cold water supply

The specific dimensions of each system must be determined according to personal preferences, frequency of usage and the number of users. Operating pressure max. 1 MPa. Recommended operating pressure: 0.2-0.5 MPa (1 MPa = 10 bar = 147 PSI). Hot water temperature: max. 60 °C. When calculating the storage and drain capacity, bear in mind that, depending on which showers are combined, up to 48 l/min of mixed water are needed at 0.3 MPa.

**Attention:** This product cannot be used in combination with continuous flow water heaters. Large differences in pressure between the cold and hot water outlets must be equalized.

### 2. Shower feed pipes

Function box: 2 x G<sup>3</sup>/<sub>4</sub> hot/cold

Rainfall: 3 x G<sup>1</sup>/<sub>2</sub> mixed water  
(if flow pressure < 3 bar G<sup>3</sup>/<sub>4</sub>)

Hand shower: 1 x G<sup>1</sup>/<sub>2</sub> mixed water

Side showers: 1 x G<sup>3</sup>/<sub>4</sub> mixed water

### 3. Hansgrohe RainBrain connecting bridge

The connecting bridge serves as a base for the function box, and as a connection for both the hot and cold water feed pipes and the five shower feed pipes. Installation is carried out during the construction phase.

**Attention:** The connecting bridge must be mounted perpendicular to the vertical feed pipes, rinsed and checked in accordance with the applicable regulations and connected to the equipotential bonding grid.

Connection threads:

2 x G<sup>3</sup>/<sub>4</sub> internal thread for hot and cold water connection

### 4. Hansgrohe RainBrain function box

The function box houses: Electronic temperature control, water flow control if applicable, five magnetic valves to control the shower functions, power supply unit, the electronic control system and lighting control. Proper installation of the function box and the connecting bridge requires that an appropriate installation space must be reserved (minimum safety zone two).

**Attention:** It is essential that the function box is easily accessible for maintenance.

The function box is connected to the control panel in the shower area via a 7 m cable. The connection cable is laid in a Ø 25 mm PE empty conduit. The function box is mounted during the finishing phase of the bathroom.

Power supply: 230 V/50 Hz direct connection.

### 5. Hansgrohe RainBrain installation housing for the control panel

The installation housing serves as a base for the control panel and is installed during the construction phase. The required installation depth is 84 mm. An empty Ø 25 mm conduit (control cable) must be laid between the installation housing and the function box, and a Ø 20 mm empty conduit (audio cable) must be laid between the function box and the audio amplifier. The control panel is not inserted into the installation housing until the finishing phase of the bathroom.



RainBrain®

Control cable: 7 m long, Ø 25 mm PE empty conduit; audio cable: 7 m long, Ø 20 mm PE empty conduit.

## 6. Hansgrohe RainBrain control panel

The control panel for controlling the different shower functions is inserted into the installation housing during the finishing phase of the bathroom.

## 7. Hansgrohe Raindance Rainfall

Quick and simple installation of the Raindance Rainfall is facilitated by using the iBox universal. Considering the exceptional length and weight of this overhead shower, the iBox universal ensures that the Raindance Rainfall is securely mounted and sits perfectly on the wall (product not included in delivery).

**Attention:** The net weight of the shower without water is 12 kg. Please ensure sufficient wall reinforcement at point of installation, especially in drywall construction!

The mixed water is fed through G ½/G ¾ feed pipes into the bottom opening and two side openings of the iBox universal. Another brass pipe (approx. 10 cm long) is screwed into the fourth (upwards-pointing) opening of the iBox universal and attached to the wall with a pipe clamp. This provides additional stability. The bottom feed pipe is also secured with a pipe clamp. For plastic pipes, an additional brass nipple must be used. The pre-assembled overhead shower panel, including the pre-attached wall escutcheon, is then simply slid onto the iBox universal and screwed on at the sides. Finished!

**Attention:** The shower must be installed, rinsed and checked in accordance with the applicable regulations in order to ensure proper shower function!

## 8. Hansgrohe Fixfit hose connection

# 27453000 Fixfit S hose connection G ½

## 9. Hansgrohe Raindance AIR 100 side showers

# 28477000 Raindance AIR 100 side showers G ½

## 10. Hansgrohe Raindrain XXL waste system

Floor drain (without shower tray): DN70 drain pipe Drain for shower tray:

# 60067000 Raindrain 90 XXL complete set

Drain capacity 51 l/min (damming height 15 mm) complies with DIN12056

**Attention:** The drain capacity must be greater than 50 l/min

## 11. Audio amplifier

The Hansgrohe RainBrain control panel provides a standard signal (L, R, Audio GND) with OdBu level (0.775 V).

To complement the Hansgrohe RainBrain we recommend the Axor Starck loudspeakers (# 40874,-000).

Power supply: 230 V/50 Hz socket

## 12. Lighting control set

For external lighting

Power supply: 230 V/50 Hz

direct connection

Maximum load: 500 W

Connection cable: 10 m long

# 27189000 Hansgrohe RainBrain lighting control set

## 13. Junction box for operating voltage

Function box, lighting control set (optional) and amplifier (optional) require a 230 V/50 Hz power supply.



# Product overview




control panel pure chrome



control panel white chrome



Function box




### RainBrain finish set with water flow control

Consisting of control panel with TouchScreen user interface, function box with electronic temperature control, water flow control, 5 magnetic valves and electronic control system (power supply 230 V/50 Hz)  
 pure chrome # 15842000  
 white chrome # 15842400



### RainBrain finish set without water flow control

Consisting of control panel with TouchScreen user interface, function box with electronic temperature control, 5 magnetic valves and electronic control system (power supply 230 V/50 Hz)  
 pure chrome # 15841000  
 white chrome # 15841400

to be combined with:  
 RainBrain basic set  
 # 15840180  
 Lighting control set  
 # 27189000



all dimensions in mm




**RainBrain basic set**

Consisting of installation housing for the control panel, connection block with integrated shut-off device and dirt filter for G $\frac{3}{4}$  hot/cold water feed pipes, 5 x G $\frac{3}{4}$  connections for the showers and quick connectors for mounting the installation box, 7 m  $\varnothing$  25 mm PE empty conduit for the control cable from control panel to installation box, 7 m  $\varnothing$  20 mm PE empty conduit for audio cable  
# 15840180




**RainBrain Lighting control set**

Power supply: 230 V/50 Hz Maximum load: 500 W consisting of relay lighting control, 7 m connection cable  
# 27189000




all dimensions in mm



all dimensions in mm



# The RainBrain® function box: technical specifications



The core of the Hansgrohe RainBrain is the function box. It houses the electronic temperature control, water volume control, five magnetic valves to control the shower functions, a power supply unit and the electronic control system. The function box with its connecting bridge can be installed either directly onto the wall or in a designated installation space. The installation of the function box must be carried out within safety zone two. It is also necessary to ensure that the function box is left accessible for maintenance.

## 1. Installation space

Basic installation:  
470 mm x 570 mm x 95 mm  
Comfort installation:  
650 mm x 570 mm x 95 mm

## 2. Control panel with installation housing

Dimensions: 136 mm x 244 mm  
Installation depth: 84 mm

## 3. Function box

Dimensions: 463 mm x 313 mm  
Installation depth: 83 mm  
Power supply: 230 V/50 Hz

## 4. Connecting bridge

Dimensions: 400 mm x 96 mm  
Installation depth: 83 mm

## 5. Lighting control set\*

Dimensions: 94 mm x 94 mm  
Installation depth: 57 mm  
Power supply: 230 V/50 Hz

## 6. Audio amplifier\*

Power supply: 230 V/50 Hz

## 7. Junction box for operating voltage\*

Dimensions: 75 mm x 75 mm  
Installation depth: 57 mm  
Power supply: 230 V/50 Hz

## 8. Loud speakers\*

## 9. Lighting\*

\* These products are not included in delivery.

Hansgrohe overhead showers and shower systems combine design excellence with technologies that make our products the most innovative on the market. This brochure offers you all the relevant information for the planning and installation of the shower systems presented here: measurements, flow rate charts, planning and installation instructions as well as mounting tips from our technicians.

We did our utmost to ensure that the printing of this brochure was friendly to the environment. By using a new kind of paper we were able to reduce the CO<sub>2</sub> emissions for the production process by more than thirty percent. You too can contribute to the protection of our environment by passing on the brochure to others when you've finished reading it, or by recycling it.

To find out more, please visit  
[www.hansgrohe-int.com](http://www.hansgrohe-int.com)



**Argentina** – Hansgrohe S.A. · Av. del Libertador 14.323 · Martínez · B1640APB · Buenos Aires  
 Tel. +54 11 4733 2400 · Fax +54 11 4733 2499 · [info@hansgrohe.com.ar](mailto:info@hansgrohe.com.ar) · [www.hansgrohe.com.ar](http://www.hansgrohe.com.ar)

**Headquarter** – Hansgrohe AG · P.O. Box 1145 · D-77757 Schiltach  
 Tel. +49 7836 51-0 · Fax +49 7836 51-1300 · [info@hansgrohe.com](mailto:info@hansgrohe.com) · [www.hansgrohe.com](http://www.hansgrohe.com)

**India** – Hansgrohe India (pvt.) Ltd. · Office Nos. 601 - 604 · Sky Station · Viman Nagar · 411 016 Pune · Maharashtra · India  
 Tel. +91 20 6625 9595 · [info@hansgrohe.in](mailto:info@hansgrohe.in) · [www.hansgrohe.in](http://www.hansgrohe.in)

**Mexico** – Hansgrohe · Col. Lomas de Santa Fe · 01210 México, D.F. · Tel. +52 55 5261-4191 · Fax +52 55 5261-4199  
[info@hansgrohe.com.mx](mailto:info@hansgrohe.com.mx) · [www.hansgrohe.com.mx](http://www.hansgrohe.com.mx)

**South Africa** – Hansgrohe South Africa (Pty) Ltd. · P.O. Box 2912 · 136 Walton Road  
 Carlswald Midrand · ZA-1685 Halfway House · Tel. +27 11 468 11-50 · Fax +27 11 468 11-52  
[sales@hansgrohe.co.za](mailto:sales@hansgrohe.co.za) · [www.hansgrohe.co.za](http://www.hansgrohe.co.za)

